

Features

- Compatible with other members of the Model 80 Series
- The only 10-turn precision potentiometer in a modular panel control package
- Up to 2 sections available
- RoHS compliant*

Additional Information

Click these links for more information:

PRODUCT | TECHNICAL LIBRARY | INVENTORY | SAMPLES | CONTACT

83/84 – 5/8 ″ Square 10-Turn Panel Control

Initial Electrical Characteristics[1]

	Wirewound Element (J Taper)	Hybritron® Element (K Taper)
Standard Resistance Range	200 to 100 K ohms	1 K to 100 K ohms
Total Resistance Tolerance	±5 %	±10 %
Independent Linearity	±0.25 %	±0.25 %
Absolute Minimum Resistance (J Taper)	1.0 ohm or 0.1 % (whichever is greater)	–
Effective Electrical Angle	3600 ° +10 °, -0 °	3600 ° +10 °, -0 °
Dielectric Withstanding Voltage (MIL-STD-202, Method 301)		
Sea Level	1,000 VAC minimum	1,000 VAC minimum
Insulation Resistance (500 VDC)	1,000 megohms minimum	1,000 megohms minimum
Power Rating (Voltage Limited By Power Dissipation or 350 VAC, Whichever Is Less)		
+70 °C	1 watt	1 watts
+125 °C	0 watt	0 watt
Theoretical Resolution	See table	Essentially infinite
End Voltage (K Taper)	–	0.2 % of applied voltage
Noise (J Taper)	100 ohms ENR maximum	–
Output Smoothness (K Taper)	–	0.15 % maximum

Environmental Characteristics[1]

Operating Temperature Range	+1 °C to +125 °C	+1 °C to +125 °C
Storage Temperature Range	-55 °C to +125 °C	-55 °C to +125 °C
Temperature Coefficient Over Storage Temperature Range	±50 ppm/°C	±100 ppm/°C
Vibration	15 G	15 G
Total Resistance Shift	±2 %	±2 %
Voltage Ratio Shift	±0.2 %	±0.2 %
Wiper Bounce	0.1 millisecond maximum	0.1 millisecond maximum
Shock	50 G	50 G
Total Resistance Shift	±2 %	±2 %
Voltage Ratio Shift	±0.2 %	±0.2 %
Wiper Bounce	0.1 millisecond maximum	0.1 millisecond maximum
Load Life	1,000 hours	1,000 hours
Total Resistance Shift	±2 % maximum	±5 % maximum
Rotational Life (No Load)	1,000,000 shaft revolutions	4,000,000 shaft revolutions
Total Resistance Shift	±5 % maximum	±5 % maximum
Moisture Resistance (MIL-STD-202, Method 103, Condition B)		
Total Resistance Shift	±2 % maximum	±5 % maximum
Insulation Resistance (500 VDC)	100 megohms minimum	100 megohms minimum
IP Rating	IP 40	IP 40

Mechanical Characteristics[1]

Stop Strength	33.90 N-cm (48.0 oz.-in.) minimum
Mechanical Angle	3600 ° +15 °, -0 °
Torque	
Starting	Running torque plus 0.7 N-cm (1.0 oz.-in.) maximum
Running (1 or 2 Section)	0.18 to 1.41 N-cm (0.25 to 2.0 oz.-in.)
Mounting (Torque on Bushing)	1.7-2.0 N-m (15-18 lb.-in.) maximum
Shaft Runout	0.15 mm (0.006 in.) T.I.R.
Shaft End Play	0.36 mm (0.014 in.) T.I.R.
Shaft Radial Play	0.13 mm (0.005 in.) T.I.R.
Weight (Single Section)	21 gm (0.75 oz.)
(Each Additional Section)	18 gm (0.65 oz.)
Terminals	Printed circuit terminals or solder lugs
Soldering Condition	Recommended hand soldering using Sn95/Ag5 no clean solder, 0.025 ″ wire diameter. Maximum temperature 399 °C (750 °F) for 3 seconds. No wash process to be used with no clean flux
Marking	Manufacturer's trademark, wiring diagram, date code and resistance, manufacturer's part number.
Ganging (Multiple Section Potentiometers)	2 cup maximum
Hardware	One lockwasher and one mounting nut is shipped with each potentiometer; locking bushing versions are shipped with one additional locking nut (Bushing A: H-37-2 & H-38-2; Bushing B: H-37-2, H-38-2 & H-38-4; Bushing C: H-37-1 & H-38-1; Bushing E: H-37-1, H-38-1 & H-38-3; Bushing J: H-37-2 & H-38-2; Bushing N: H-37-1 & H-38-1; Bushing R: H-37-4 & H-38-9; Bushing U: H-37-3 & H-38-8)

NOTE: Model 83/84 performance specifications do not apply to units subjected to printed circuit board cleaning procedures.

[1]Electrical specifications tested at 250 RPM, at room ambient: +25 °C nominal.

WARNING
Cancer and Reproductive Harm
www.P65Warnings.ca.gov

*RoHS Directive 2015/863, Mar 31, 2015 and Annex.

Specifications are subject to change without notice. Users should verify actual device performance in their specific applications. The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

83/84 – 5/8 ″ Square 10-Turn Panel Control

BOURNS®

Wirewound Resolution Table

Resistance (Ohms)	Resolution (Nom.) (%)
200	.048
500	.037
1 K	.032
2 K	.031
5 K	.023
10 K	.020
20 K	.015
50 K	.012
100 K	.010

Dimensional Drawings

Dual Section Model 84 Solder Lugs



Note: The Models 83/84 dimensions for dual section assembly are for either single or dual concentric shaft styles.

Dual Section Model 83 PC Pins



DIMENSIONS: MM / (INCHES)

Suggested Panel Layout



BUSHING	DIM A
A, B & J	9.91 (.39)
C, E & N	6.73 (.265)
R & S	10.5 (.413)
U	7.5 (.295)

DIMENSIONS: MM / (INCHES)

ANTI-ROTATION LUG	DIM B	DIM C	DIM D	DIM E
A	7.75 (.305)	N/A	N/A	2.49 (.098)
B	7.75 (.305)	7.75 (.305)	N/A	2.49 (.098)
C	N/A	7.75 (.305)	N/A	2.49 (.098)
E	13.49 (.531)	N/A	N/A	3.45 (.136)
F	N/A	N/A	7.75 (.305)	2.54 (.100)
J	9.53 (.375)	N/A	N/A	2.54 (.100)

Date Code Description



Specifications are subject to change without notice.
Users should verify actual device performance in their specific applications.
The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

Product Dimensions

PC Pin Model 83



Solder Lug Model 84





Shaft Flat Orientation



"A" Bushing
3/8 " (9.53 mm) Dia. Plain - Single Shaft



"B" Bushing
3/8 " (9.53 mm) Dia. Plain - Single Shaft



"C" Bushing
1/4 " (6.35 mm) Dia. Plain - Single Shaft



"E" Bushing
1/4 " (6.35 mm) Dia. Locking - Single Shaft



"A" Bushing
3/8 " (9.53 mm) Dia. Plain - Concentric Shaft



"C" Bushing
1/4 " (6.35 mm) Dia. Plain - Concentric Shaft



Locating Lug Options - All Model 80 Series



TOLERANCES EXCEPT AS SHOWN: DECIMALS .XXX ± .127 (.005)
.XX± .38 (.015)
ANGLE ± 5 °
FRACTIONS ± 1/64

DIMENSIONS: MM / (INCHES)

NOTE: "D" OPTION - NO A/R LUG. OTHER LOCATING LUG OPTIONS AVAILABLE. FOR DETAILS CONSULT FACTORY.

Specifications are subject to change without notice.
Users should verify actual device performance in their specific applications.
The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

Hardware

LOCKWASHER H-37-1



LOCKWASHER H-37-2



LOCKWASHER H-37-3



LOCKWASHER H-37-4



NUT H-38-1



NUT H-38-2



NUT H-38-8



NUT H-38-9



DIMENSIONS: MM / (INCHES)

LOCKNUT H-38-3



LOCKNUT H-38-4



LOCKNUT H-38-10



Specifications are subject to change without notice.
Users should verify actual device performance in their specific applications.
The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

83/84 – 5/8 ″ Square 10-Turn Panel Control

BOURNS®

How To Order

83	A	1	A	-	B	28	-	J	15	L

RoHS IDENTIFIER	
L	Compliant

ANTI-ROTATION LUG	
A	**Single .305 R, 90 °CW**
B	Double .305 R, 90 ° & 270 °CW
C	Single .305 R, 270 °CW
D	**No Lug**
E	Single .531 R, 90 °CW
F	Single .305 R, 180 °CW
J	Single .375 R, 90 °CW

# SECTIONS	
1	**Single**
2	**Double**
3	Triple

SHAFT LENGTH (FMS)		AVAILABLE ONLY IN BUSHING
Code	**Description**	**Code**
12	3/8 ” L	C, N, J
16	1/2 ” L	A, C, J, N
20	5/8 ” L	A, B, C, E, J, N
24	**3/4 ” L**	A, B, C, E, J, N
28	**7/8 ” L**	A, B, C, E, J, N
32	1 ” L	A, B, C, E, J, N
36	1-1/8 ” L	A, B, C, E, J, N
40	1-1/4 ” L	A, B, C, E, J, N
Metric		
10	10 mmL	U
13	13 mmL	U
16	16 mmL	R
19	19 mmL	R
22	**22 mmL**	R, U
30	30 mmL	R
42	42 mmL	R
50	50 mmL	R

ELEMENT TAPER TYPE/TOLERANCE		RESISTANCE CODE VALUE IN OHMS	
		J	K
(J)	**Linear Wirewound 10-Turn ±5 %**	**(06) - 200**	**(10) - 1 K**
		(08) - 500	(11) - 2 K
(K)	Linear Hybritron® Elements 10-Turn ±10 %	**(10) - 1 K**	(13) - 5 K
		(11) - 2 K	(15) - 10 K
		(13) - 5 K	(16) - 20 K
		(15) - 10 K	(18) - 50 K
		(16) - 20 K	(20) - 100 K
		(18) - 50 K	
		(20) - 100 K	

BUSHING	
A	**Plain 3/8 ” (9.53 mm) D x 3/8 ” (9.53 mm) L**
B	Locking 3/8 ” (9.53 mm) D x 1/2 ” (12.7 mm) L
C	**Plain 1/4 ” (6.35 mm) D x 1/4 ” (6.35 mm) L**
E	Locking 1/4 ” (6.35 mm) D x 1/2 ” (12.7 mm) L
J	Plain 3/8 ” (9.53 mm) D x 1/4 ” (6.35 mm) L
N	Plain 1/4 ” (6.35 mm) D x 3/8 ” (9.53 mm) L
R	**Plain 10 mm D x 9 mm L**
U	Plain 7 mm D x 6 mm L

MODEL	
83	**10-Turn, PC Pins**
84	**10-Turn, Solder Lugs**

SHAFT TYPE		AVAILABLE ONLY IN LENGTHS (CODE)	AVAILABLE ONLY IN BUSHINGS (CODE)
A	Single Plain 1/4 ” (6.35 mm) D	16,20,24,28	A, B, J
B	**Single Slotted 1/4 ” (6.35 mm) D**	**16,20,24,28**	**A, B, J**
C	Single Flatted 1/4 ” (6.35 mm) D	20,24,28	A, B, J
E	**Single Slotted 1/8 ” (3.18 mm) D**	**12,16,20,24,28**	**C, E, N**
F	Single Flatted 1/8 ” (3.18 mm) D	Consult Factory	C, N
G	Dual Concentric Plain 1/4 ” (6.35 mm) D - 1/8 ” (3.18 mm) D Outer Operates Section 1	36,40	A, J
K	Dual Concentric Plain 1/8 ” (3.18 mm) D - 5/64 ” (1.98 mm) D Outer Operates Section 1	32,36	C, N
L	Dual Concentric Plain 1/4 ” (6.35 mm) D - 1/8 ” (3.18 mm) D Outer Operates Section 1/2	36,40	A, J
M	Dual Concentric Plain 1/8 ” (3.18 mm) D - 5/64 ” (1.98 mm) D Outer Operates Section 1	32,36	C, N
N	Dual Concentric Plain 1/4 ” (6.35 mm) D - 1/8 ” (3.18 mm) D Outer Operates Section 1/2/3	36,40	A, J
P	Dual Concentric Plain 1/8 ” (3.18 mm) D - 5/64 ” (1.98 mm) D Outer Operates Section 1/2	32,36	C, N
R	**Single Slotted 6 mm D**	**16,19,22,50**	**R, S**
T	Single Slotted 4 mm D	10, 13, 22	U
V	Dual Concentric Plain 6 mm D - 3 mm D Outer Operates Section 1	30, 42	R

Boldface features are Bourns standard options.
All others are available with higher minimum order quantities.

REV. 04/25

Specifications are subject to change without notice.
Users should verify actual device performance in their specific applications.
The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

Legal Disclaimer Notice

BOURNS®

This legal disclaimer applies to purchasers and users of Bourns® products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns® products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns® products.

The characteristics and parameters of a Bourns® product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain types of applications are based on Bourns' knowledge of typical requirements in generic applications. The characteristics and parameters of a Bourns® product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns® product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns® product also can and do vary in different applications and actual performance may vary over time. Users should always verify the actual performance of the Bourns® product in their specific devices and applications, and make their own independent judgments regarding the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real world conditions.

Unless Bourns has explicitly designated an individual Bourns® product as meeting the requirements of a particular industry standard (e.g., IATF 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns® product to meet the requirements of such industry standard or particular qualification. Users of Bourns® products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns® products are not recommended, authorized or intended for use in nuclear, lifesaving, life-critical or life-sustaining applications, nor in any other applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage. Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any Bourns® products in such unauthorized applications might not be safe and thus is at the user's sole risk. Life-critical applications include devices identified by the U.S. Food and Drug Administration as Class III devices and generally equivalent classifications outside of the United States.

Bourns expressly identifies those Bourns® standard products that are suitable for use in automotive applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard products in an automotive application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk. If Bourns expressly identifies a sub-category of automotive application in the data sheet for its standard products (such as infotainment or lighting), such identification means that Bourns has reviewed its standard product and has determined that if such Bourns® standard product is considered for potential use in automotive applications, it should only be used in such sub-category of automotive applications. Any reference to Bourns® standard product in the data sheet as compliant with the AEC-Q standard or "automotive grade" does not by itself mean that Bourns has approved such product for use in an automotive application.

Bourns® standard products are not tested to comply with United States Federal Aviation Administration standards generally or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aircraft or space applications. Bourns expressly identifies Bourns® standard products that are suitable for use in aircraft or space applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard product in an aircraft or space application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk.

The use and level of testing applicable to Bourns® custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns® custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns® standard products shall also apply to such Bourns® custom products.

Users shall not sell, transfer, export or re-export any Bourns® products or technology for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns® products or technology in any facility which engages in activities relating to such devices. The foregoing restrictions apply to all uses and applications that violate national or international prohibitions, including embargos or international regulations. Further, Bourns® products and Bourns technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns® products may not, without prior authorization from Bourns and/or the U.S. Government, be resold, transferred, or re-exported to any party not eligible to receive U.S. commodities, software, and technical data.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties, including implied warranties of fitness for particular purpose, non-infringement and merchantability.

For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:

Web Page: http://www.bourns.com/legal/disclaimers-terms-and-policies

PDF: http://www.bourns.com/docs/Legal/disclaimer.pdf

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Bourns:

84A1E-C24-J10 84A1D-B12-J10 83C1D-E16-J20 84C1D-E12-K16 84C1D-E12-K18 83A1D-B24-K13 83A1D-B24-K15 84A1A-B28-J13 84C1A-E20-J13 84C1A-E20-J10 84A1A-B28-J10 84C1A-E20-J18 84C1A-E20-J15 84N1D-E24-J15 83A1D-B20-K15 84J1A-B16-J15 84J1D-B16-J16 84A1D-C24-K13 83C1A-E24-J15 83C1A-E24-J10 84C1A-E28-J13 84C1A-E28-J16 83A1A-A24-K15 84A1A-B36-J13 84A1D-C20-J11 84J1A-B24-J15 84J1A-C24-J08 83C1D-E16-J15 83C1D-F16-J10 83J1D-B24-J15 84J1D-B20-J08 83C1D-E20-J13 83A1D-C28-J10 83A1D-B28-J16 83A1D-B28-J10 83A1D-B28-J18 84C1D-E16-J08 83C1D-F20-J15 83C1D-E20-J15 83C1D-E20-J11 83A1D-B28-J15 83A1D-B28-J13 83A1D-B28-J11 83A1D-B28-K16 83A1D-B28-K15 83C1D-E20-K18 83C1D-E20-K15 83A1D-B28-K13 84C1C-E28-J16 84C1C-E28-J18 84C1D-E20-J15 84C1D-E20-J20 84A1D-B28-J13 84A1D-B28-J10 84A1D-B28-J18 84A1D-A28-J20 84C1D-E08-J15 83A1D-B24-J10 83A1D-B12-J10 83N1D-E28-J10 84C1A-E24-J18 84C1A-E24-J10 83A1D-C24-J20 84C1A-E24-J13 83A1D-B24-J08 83A1D-B24-J20 84C1A-E24-J15 84C1D-E12-J15 84C1A-E24-J16 83A1A-A24-J13 83A1A-A24-J18 83C1A-E28-K16 84A1D-B28-K11 84A1D-B28-K15 84C1D-F40-J10 84C1D-F40-J16 84C1E-E24-J16 84A1D-B24-J15 84C1D-E28-J13 84A1A-B28-K15 83A2D-B28-J18/J18 83C1D-E20-J18 83A1D-C28-K13 84A2A-G36-J11/J11 83A1A-B24-J15L 83A1D-B28-J20L 83A1D-C28-K13L 83C1D-E20-J18L 84A1A-B28-J15L 84A1A-B28-K15L 84A1A-C24-J15L 84C1E-E24-J16L 83A1A-B24-J18L 83A1A-B28-J10L 83A1A-B28-J13L 84A1A-B28-J10L 84A1A-B28-J13L 84C1A-E24-J13L 84C2A-E24-J15/J15L 84C1D-F40-J15