


REV	CONTENT	CHK	DATE
V0.0	CONTENT	SYJ	25.04.11

Electrical :

1.Operating Temperature : -40℃~+105℃



2.RoHS Compliance

3."★" is the key quality control point



① Cover plate ④ Connection quantity

⑤ Color: GY-Grey
 BU-Blue
 BK-Black
 GN-Green
 OG-Orange
 RD-Red
 YE-Yellow
 WH-White
 PE-Yellow & Green
 BE-Beige



Total Pitch Tolerances in mm									Nominal dimension range in mm									$\perp$		$\equiv$	$-$	$//$				
over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 250	over 350	over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 0	over 10	all	over 0	over 100	over 150			
to 30	to 53	to 70	to 90	to 115	to 150	to 250	to 350	to 500	to 30	to 53	to 70	to 90	to 115	to 150	to 200	to 250	to 320	to 10	to 10		to 100	to 150	to 150			
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.60	±0.70	±0.85	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.5			
6									5									4								

1	HOUSING		XX		1	PA66 UL94V-0		SEE NOTE	
ITEM	NAME OF PART		NO. OF PART		Q"TY	MATERIAL		NOTE	
DWG.	SYJ	DATE	25.08.04		SIZE	A4	UNITS	mm	SHEET/OF 1 / 1
CHK.		DATE			SCALE	1:1		D-GP6-3-X	
APP.		DATE			NAME				
 宁波冠泰电子有限公司 NINGBO GOLTEN ELECTRONICS CO., LTD.					DWGNO.	XXXXX			
		2			1				